



(864) 573-7400 PHONE
(864) 585-3635 FAX
info@trucktanks.com EMAIL

P.O. Box 2807
Spartanburg, SC 29304
www.trucktanks.com

STOCK #42012BL

TANK: 4200 Gallon aluminum tank with 4-compartments holding 500-2000-1000-700 gallons front to rear. Tank has double bulkheads, emergency valves, 4" lines to the side terminating in bottom loading adapters and 2" male dry break adapters. Tank is an AL5D style with trim fenders, (1) 65" double door cabinet, (2) 6" hose tubes, (1) gauge stick holder and 16" lift out manhole covers with 10" fills. Tank has rear canopy equipment area and rear platform ladder.

This model tank is a modified "Bikini" style with full rear head behind a large rear equipment canopy, which accommodates two inverted hose reels. This canopy opens both to the curb and driver's side with rollers/guides on both sides for ease of delivery. The meter box, directly under the canopy, is of heavy-duty steel and has aluminum cover with (2) aluminum fold down doors with slam lock hardware.

BOTTOM LOADING / VAPOR RECOVERY: (4) Openable loaders, (4) gravity drop adapters with keeper chains, (4) dust caps, (4) interlock air operated valve mounted on each bottom loading adapter, (4) deflectors which control splash above sumps, (4) Scully probes, (4) 3-1/2" air vents with hoods, (1) vapor recovery line to the rear, (1) 4" Betts inbreathing vent, (1) 4" Betts outbreathing vent, (1) Scully On-Board control monitor, (1) Scully SJ-6 socket for thermistor, (1) Scully SJ-6S socket for thermistor, (1) Scully static grounding bolt for Groundhog system.

EQUIPMENT: (2) Sets of pumping equipment located in the rear including: (2) 2-1/2" Blackmer pumps, (2) Liquid Controls 100 GPM rated meters with auto stops and ticket printers, (2) inverted Hannay hose reels with 1-3/8" x 100' hoses, (2) 1-1/2" nozzles, (2) 2" jumper hoses with 2" female dry break couplers, (2) clutch shift power take offs with rear mount controls, and (1) 5# fire extinguisher. There is a 2" pump-off line on each system, (2) meter lights and (1) swivel work light.

CHASSIS: 2004 International 7500 with HT530 315 HP diesel engine, 10-speed transmission, 16,000# front axle, 46,000# rear axle, double channel frame, air suspension, air brakes, steel rear wheels, aluminum front wheels, 22.5 tires, air ride high back driver seat, fixed high back passenger seat, (1) 55-gallon fuel tank, air horn, and West Coast with convex mirrors. Truck has air conditioning, AM/FM/Cassette radio, vertical exhaust, chrome grill and bumper, air ride cab, air dryer, exhaust brake, cruise control, block heater, locking differential and front tow hooks. Truck has approximately 193,900 Miles

Chassis is white. Tank is natural aluminum.

Tank is MC 406 certified to haul gasoline and all other petroleum products. Current V-K-I-P tests are included.





